

**CHOOSE YOUR
CORIOLIS FLOW METER**

0.1%
Liquid Mass
Flow

**Smart Meter
Verification™**

2/4
Wire Cabling

Data Historian

**Bluetooth/
WIFI Config**

**Drainable
3A & EHEDG**

SIL ✓
Functional
Safety



G-Series



F/H-Series



ELITE

Line Size	5 line sizes ¼" - 3" DN6 to DN80	7 sizes ¼" - 3"	14 sizes 1/10" - 14"
Turndown	Moderate 8:1	Competitive 20:1	Market Leading > 30:1
Liquid Flow	±0,1%	±0,05%	±0,05%
Gas Flow	±0,5%	±0,35%	±0,25%
Density	±5 kg/m3	±0.5 - 2 kg/m3	±0.2 - 0,5 kg/m3
High Temp	150°C	204°C - 350°C	350°C - 427°C
2 Phase Flow	—	◐ Suitable Low Hz	● Preferred Ultra Low Hz
Cryogenic	—	◐ ETO	● -240°C
Corrosive Material	—	● C22	● C22
Custody Transfer	—	◐ OIML MID Liquid	● OIML MID Liquid + Gas
Custom Calibration	—	—	● Available ISO17025
Advanced Measurement Software	—	—	● PWL 0,1% Gas APM

**Market Leading
Compactness**
Weight / Flag / F2F



**Market Leading
Flow Performance**
Temperature & Pressure
Effects / Viscosity / Entrained Air /
Zero Stability